


3516C 60Hz Enclosure



Sound Attenuated (SA) Level 1 Enclosure



Sound Attenuated (SA) Level 2 Enclosure

Images shown may not reflect actual configuration

	SA Level 1	SA Level 2
Standby Rating - eMW	2.0	2.0
Sound Pressure Level - dBA	79 @7m	74 @7m
Ambient Capability - °C (°F)	45 (113)	45 (113)
Wind Rating - mph	120	120
Footprint: Length x Width - ft	45' 6" x 8' 9"	45' 6" x 8' 9"
Fuel Tank Run time - hours	24	24
Available Voltages - V	480	480

Features

Construction

- Galvanneal construction
- Enclosed muffler
- NEC Code Compliant

Integral Fuel Tank Base

- UL142 Listed
- 24 hour run time @ 2.0 eMW

Cooling System

- Horizontal JW & ATAAC Radiator
- 1 x electric cooling fans with individual MCB's /alarms

Access Doors

- Personnel doors - double doors on right side, single door on left side
- Maintenance doors - 2 doors on left side for radiator and air intake access

Certifications

- UL 2200 Listed
- UL 142 Listed
- CSA

Options

Construction


- Skid base - No fuel tank
- Motorised louvres

General

- Jacket water heaters
- Space heater


Dimensions

Sound Attenuated Level 1



Length (A) mm (in)	Width (B) mm (in)	Height with tank (C) mm (in)	Height with skid mm (in)
13868 (546.0)	2671 (105.2)	4231 (166.6)	3926 (154.6)

Sound Attenuated Level 2



Length (A) mm (in)	Width (B) mm (in)	Height with tank (C) mm (in)	Height with skid mm (in)
13868 (546.0)	2671 (105.2)	5007 (197.1)	4702 (185.1)

www.cat.com/electricpower

©2024 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.