



**Prime 30 kVA (24 kW)
50/60 Hz Switchable
Best Specific Fuel Consumption**

Image shown may not reflect actual configuration.

Specifications

Frequency Hz	Speed (rpm)	Voltage	Prime		Output Amps (A)	Breaker Rating (A)
			kVA	kW		
50	1500	415 / 240V	30	24	42	63
		400 / 230V	30	24	43	
		380 / 220V	30	24	46	
60	1800	480 / 277V	38.5	28.6	43	63
		440 / 254V	38.5	28.6	47	
		380 / 220V	34.5	27.6	52	
		240 / 139V	38.5	28.6	86	125
		220 / 127V	38.5	28.6	94	

Cat® C3.3 Diesel Engine	Metric	Imperial (English)
Configuration	Inline 3-cylinder, 4-Stroke-Cycle, Water Cooled, Diesel	
Bore	105 mm	4.13 in
Stroke	127 mm	5.00 in
Displacement	3.3 L	201 in ³
Aspiration	Naturally Aspirated (NA)	
Compression Ratio	19.25:1	
Engine rpm	1500-1800	
Aftercooler Type	N/A	
Turbocharger	N/A	
Fuel System	Direct Injection, Rotary Pump	
Governor Type	Electronic Governor, Mechanical Actuator	
Fuel	See Fuel Specification Table	

Benefits & Features

Rental-ready Features

- 24 hr dual wall fuel tank with tie down points and robust skid plate base
- Forklift pockets
- Externally certified single point lift
- Coolant and oil drains piped to baseframe
- Externally certified spark arrest silencer
- 50/60 Hz frequency switch via terminal link
- Optimized cable entry for easy hook-up
- Robust busbar connection for lugged cable connection
- Sound isolated side mounted control panel with integrated power distribution access
- AC protected by limit switch on distribution door

Fuel/Emissions Strategy

- Best fuel efficiency

Single-source Supplier

- Factory designed and fully prototype tested with torsional vibration analysis available
- ISO 9001:2000 compliant facility

Cat C3.3 Diesel Engine

- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic governor, mechanical actuator

Cat EMCP 4.2B Control Panel

- Fully featured power metering, protective relaying, engine/generator control and monitoring
- Simple user-friendly interface and navigation
- Single point interface for voltage and frequency adjustment

Optional Control Panel

- DEEP SEA DSE7320 MKII
- Fully featured power metering, protective relaying, engine/generator control and monitoring.

Cat LC1500 Generator

- Designed to match performance and output characteristics of Cat diesel engines
- Coastal insulation protection
- Self (Shunt) excitation

Available Options

- CE socket box with integrated RCBO protection
- Clipsal socket box with integrated RCBO protection
- 220-240V 3-phase 60Hz configuration available with appropriately sized breaker and power cables.
- Anti condensation heater 110V or 230V AC
- Coolant heater 110V or 230V AC
- 12V battery charger
- Permanent Magnet Generator (PMG)
- Earth leakage detection
- Lube oil sump pump

Integrated Voltage Regulator (IVR)

(with EMCP 4.2B only)

- Three-phase sensing
- Adjustable Volts-per-Hertz regulation
- Provides precise control, excellent block loading, and constant voltage in the normal operating range

Enclosure

- Galvanized sheet steel construction
- Two coat polyester powder-coated finish
- 6 access doors for improved service access
- Secure design with safety glass control panel viewing window and padlockable or keylock access doors
- Fuel fill, battery and controls accessible only through lockable access doors

Environmental Considerations

- Dual wall base tank with 110% spill containment
- Bund Level alarm
- Low noise enclosure
- Inboard mounted 3-way valve for external fuel connection

Cat Connect

- Fleet management and asset tracking*

*Subject to local certifications.

Standard Equipment

Generator

- LC1514F frame; 3-phase random wound, 12 lead, self excited, 2/3 pitch
- Coastal insulation protection (CIP)

Cat C3.3 Diesel Engine

- Naturally aspirated
- Electronic governor, mechanical actuator

Air Filter

- Air cleaner, cyclonic/paper with dust cup and service indicator

Cooling System

- Package mounted radiator with vertical air discharge
- High ambient performance
- Fully guarded pusher fan
- Low coolant level shutdown
- Coolant piped to base via radiator-mounted ball valve
- 50% glycol mix with corrosion inhibitor

Charging System

- Charging alternator; 12V, heavy duty with integral regulator and belt guards

Starting System

- Single 12V electric starting motor
- Single 12V 950CCA maintenance-free battery with padlockable single-pole isolator switch

Fuel System

- 24hr dual wall fuel tank (based on 75% Prime load)
- Internal fuel fill
- Off-engine mounted Racor fuel water separator (30 micron) with secondary engine-mounted fuel filter
- Auxiliary connections for remote supply with 3-way valve
- 3-way valve internally mounted within banded area
- Mechanical fuel gauge
- Electronic fuel gauge with panel display, low fuel level warning and shutdown

Control Panel

- EMCP 4.2B set mounted digital controller
- 50/60 Hz frequency switch (via terminal link)
- IVR with EM10 excitation module
- Panel & enclosure mounted emergency stop

Distribution System

- Single robust steel enclosure for controls & distribution
- Separately hinged distribution door with 12V DC shunt trip safety switch
- 4 pole, 200A main circuit breaker
- Two-wire remote start/stop terminals and AC aux power connection for rapid starting

Mounting System

- Heavy duty steel baseframe with integral fuel tank (dual wall)
- Provides 110% spill containment including all on-board fluids
- Forklift pockets
- Skid plates with drag points
- Generator set soft mounted using captive vibration mounts

Enclosure

- Sound attenuating, galvanised sheet steel enclosure with exceptional noise reduction performance
- Interior walls, ceilings and ducts insulated with precision cut noise insulating materials
- Sealed quarter-turn compression latches with key or padlock capabilities
- Front and rear service access provided through hinged doors
- External single point lift
- Powder coated with Cat Rental Power decals

Exhaust System

- Integrated certified spark arresting silencer with flexible connectors
- Outlet box mounted with vertical discharge

Lube Oil System

- On-engine primary and secondary oil filters, dipstick and oil filler
- Open crankcase breather with fumes disposal container and drain point
- Oil piped to edge of baseframe with internally mounted ball valve
- 500 hour oil change requirement

General

- Factory Tested
- Full manufacturer's warranty, O&M manuals

Fuel Specifications

Specification Standard	Grade Class	Fuel Description	
EN 590	Grade A to F & Class 0 to 4	European automotive fuel (DERV)	
ASTM D975	1-D S15	U.S. special purpose light middle distillate	
		15 ppm sulphur	
ASTM D975	2-D S15	U.S. special purpose light middle distillate	
		15 ppm sulphur	
JIS K2204	No. 1	Japanese automotive diesel. Different classes correspond to season and district where used	
	No. 2		
	No. 3		
	Special No. 3		
BS 2869	Class A2	Fuel oil for agriculture and industrial engines (red diesel)	
MIL-DTL-83133 NATO F34	JP-8	Aviation kerosene fuels – acceptable when used with appropriate lubricity additive, and must meet minimum requirements of Caterpillar Specification for Diesel Fuel. The lubricity of these fuels must not exceed wear scar diameter of 0.52 mm (0.02047 in) as per ISO 12156-1	
MIL-DTL-83133 NATO F35			
MIL-DTL-5624 NATO F44	JP-5		
MIL-DTL-38219 (USAF)	JP-7		
NATO XF63			
ASTM D1655	JET A		
	JET A1		
B5-B7			Blend of biodiesel meeting EN 14214 or ASTM D6751 with EN 590 or ASTM D975 standard mineral diesel fuels.
B7-B20			

Technical Data

Cat Generator	
Frame size	LC1514F
Pitch	2/3
No. of poles	4
Excitation	Static regulated, brushless, self excited
Number of bearings	Single bearing, close coupled
Insulation	Class H
Temperature rise	125/40°C
Enclosure	Drip proof IP23
Overspeed capability — % of rated	25%
Voltage regulator	3-phase sensing with adjustable volts per hertz
Voltage regulation	Less than ± 0.5%
Wave form deviation	
Telephone Harmonic Factor (THF)	Less than 2%
Total Harmonic Content (THC)	Less than 2%

Technical Data (continued)

Cat Generator Set			
	TMI Performance No. Units	Prime – 50 Hz	Prime – 60 Hz
Power Rating	kVA (kW)	30 (24)	35.8 (28.6)
Performance Specification			
Lubricating System			
Oil pan capacity	L (gal)	7 (1.85)	7 (1.85)
Fuel System			
Fuel consumption — 100% Load	L/hr (gal/hr)	7.2 (1.9)	8.6 (2.3)
75% Load	L/hr (gal/hr)	5.6 (1.5)	6.6 (1.7)
50% Load	L/hr (gal/hr)	4.1 (1.1)	4.9 (1.3)
Fuel tank capacity	L (gal)	147 (108)	147 (108)
Running time @ 75% rating	Hr	26	22
Cooling System			
Ambient capability	°C (°F)	55 (135)	50 (122)
Engine & radiator coolant capacity	L (gal)	10.2 (2.7)	10.2 (2.7)
Engine coolant capacity	L (gal)	4.4 (1.2)	4.4 (1.2)
Air Requirements			
Combustion air flow	m ³ /min (cfm)	–	–
Exhaust System			
Exhaust flow at rated — dry	m ³ /min (cfm)	5.7 (201)	6.4 (226)
Exhaust temperature at rated kW	°C (°F)	500 (932)	520 (968)
Noise Rating (with enclosure)*			
Sound Power*			
@ 7 meters @ 75% load	dB(A)	88	89
@ 7 meters @ 100% load	dB(A)	60	62
@ 1 meter @ 75% load	dB(A)	62	63
@ 1 meter @ 100% load	dB(A)	72	73
	dB(A)	73	74

*Guaranteed sound power as per 2000/14/EC.

For full Engine & Emissions data please refer to TMI using the engine performance no.

Dimensions and Weights

Length (L) mm (in)	Width (W) mm (in)	Height (H) mm (in)	With Lube Oil & Coolant Kg (lb)	With Fuel (Full Tank), Lube Oil & Coolant Kg (lb)
2150 (84.6)	1120 (44.1)	1583 (62.3)	1230 (2712)	1385 (3053)


Socket Box Options

Sockets	15A	16A	32A	50A	63A	125A
Clipsal*	2x1ph+N+E	-	1x3ph+N+E	-	-	-
CEE Form*	-	2x1ph+N+E	1x3ph+N+E	-	-	-

* Busbar connection is standard. Distribution sockets are optional.


General Layout Images

Pictures shown may not reflect actual configuration



Control Panel & Power Distribution Layout

Item	Description
1	Steel enclosure with hinged, lockable door
2	EMCP 4.2B
3	Emergency Stop button
4	Circuit breaker. 4-pole MCB
5	Service tool connector
6	Alarm
7	Micro safety switch for busbar door
8	Main bus connection (busbars with M8 studs)
9	Main earth terminal



Ratings Definition

Designed to Meet Specifications: IISO 8528, EN 12601, EN 60204-1, ISO 3046, IEC 60034.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO 3046 standard conditions.

Prime — Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Fuel rates are based on fuel oil of 35° API {16°C (60°F)} gravity having an LHV of 42780 kJ/kg (18390 Btu/lb) when used at 29°C (85°F) and weighing 838.9 g/litre (7.001 lb/U.S. gal).

Additional ratings may be available for Specific customer requirements, contact your Caterpillar Representative for details. For information regarding Low Sulphur fuel and biodiesel capability and consult your Cat Dealer.

www.cat.com/electricpower

©2025 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow" the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.